

CALLAN DATA SYSTEMS  
EUROPEAN O.E.M. PRICE LIST  
May 1, 1981

PRODUCT	DESCRIPTION	QUANTITY	
		1-9	10-24
CD100-M	CD100 Integrated Work Station including advanced video controller (ANSI compatible) with RS232 Interface and 25 line x 80 char/line display; six slot Multibus card cage; 200 watt switching power supply; 83 key detachable keyboard with numeric keypad. 50 HZ 240 volt.	3515	2955
CD100-L	CD100 Integrated Work Station including advanced video controller (VT100/VT52 compatible) with RS232 interface and 25 line x 80 char/line display; 14 dual-height DEC LSI11 Qbus card cage; 200 watt switching power supply; 83 key detachable keyboard with numeric keypad. 50 HZ 240 volt.	3515	2955
MULTIBUS EXTENSION OPTIONS			
-01	P2 motherboard, 6 slots, address extension to 16 MBYTES, allows power fail interrupt option, includes power fail sense latch, and power fail interrupt logic.	300	250
-02	P2 wirewrap kit, 6 wirewrap connectors with threaded inserts allow custom configurations.	50	40
-03	AC low interrupt board, detects power failure and generates Multibus standard interrupt, requires -01 option.	165	140
LSI-11 CONSOLE OPTIONS			
-21	Console switch package includes HALT/ENABLE switch, LTC ON/OFF switch and RUN LED on CD100 bezel. Also includes power fail interrupt board KPV 11-A, 24 volt transformer and spare LED.	630	535
-22	Console RESET switch package includes HALT/ENABLE switch, RESET momentary switch and RUN LED on CD100 bezel.	165	140

PRODUCT	DESCRIPTION	QUANTITY	
		1-9	10-24
DISK MEMORY OPTIONS			
-61	Dual 5.25 inch minifloppy, double sided, double density, single track density (48 TPI), 40 tracks side 0, 35 tracks side 1, power cable, 34 lead signal cable, 1MBYTE storage (unformatted), controller NOT included.	1075	905
-62	Dual 5.25 inch minifloppy, double sided, double density, double track density (96 TPI), 77 tracks side 0 and side 1, power cable, 34 lead signal cable, 2MBYTE storage capacity (unformatted), controller NOT included.	1535	1285
-71	Single 5.25 inch mini Winchester drive, 6.38Mbyte unformatted, 5Mbyte formatted fixed storage AND single 5.25 inch minifloppy, double sided, double density, double track density (96TPI), 77 tracks side 0 and side 1, 1Mbyte (unformatted) removable storage. Controllers NOT included.	2805	2355
-81	Controller for dual 5.25 inch minifloppy drives, LSI 11 Q-bus compatible. Supports either -61 or -62 option. Includes RT-11 device handler for RT-11 operating system.	1200	1015
-82	Controller for dual 5.25 inch minifloppy drives, LSI-11 Q-bus compatible. Directly emulates RX02 for DEC software compatibility. Requires one dual height card slot.	1535	1285
-91	Controller for 5.25 inch, 5Mbyte Winchester, Multibus compatible; full DMA; 20-bit addressing; 256 byte or 512 byte sector; multiple sector read/write; fully automatic and transparent burst Error Correction.	1535	1285

All prices F.O.B. Westlake Village, California  
Prices subject to change without notice.  
DEC, LSI-11 are trademarks of Digital Equipment Corporation  
Multibus is a trademark of Intel Corporation.